



*Notes/技术参数:

Material 材料\ Finish表面处理

Shells&Coupling外壳 : Aluminum alloy铝合金 / Black Hard Anodizing 黑色硬质阳极氧化

Ring卡环: Aluminum alloy铝合金

Insert 插芯: Thermoplastics EN45545热塑料

Contact插针: 7x #12 pin contacts

Copper alloy 铜合金
Silver plated crimp type镀银, 压接形式

Mechanical data机械参数

Operating Temperature温度范围: -55°C ~ +125°C

Durability机械寿命: 500 cycles

Salt Spray盐雾: 200H

Electrical data电气参数:

Rated Voltage额定电压 : 900V(AC) / 1250V(DC)

Rated Current额定电流 : 23A

Withstanding Voltage耐电压: 2800VAC

Insulation Resistance: 5000 MΩ Min

Contact Resistance: Less than 1.3milliohms

REV	ECN	DESCRIPTION	DATE	MODIFIED
1		PRE-RELEASE	2018.05.03	W.Liu
2		UPDATE	2018.06.26	W.Liu

DIMENSIONS	TOLERANCES	PROJECTION	TITLE	
ANSI Y14.5M UNITS: MM CAD FILE	X ± 0.5 XX ± 0.20 ANGLES ± 0.5°		Amphenol Pcd Shenzhen	
ORIGINAL NOT FOR CUSTOMER DISTRIBUTION	THIS DOCUMENT CONTAINS PROPRIETARY INFORMATION WHICH IS THE CONFIDENTIAL PROPERTY OF AMPHENOL PCD SHENZHEN		CHKD APPD	SIZE A3
			SCALE 2:1	DWG NO. ASVG030A242PCBA
			SHEET 1 OF 1	REV 2