NACS

GCS1









REPLACEABLE COMPONENTS

1	Front housing	
2	Signal terminals	
3	PE terminal	
4	DC terminals	
5	Seal	

RATED CURRENT

370A
400A@40°C
600A Liquid cooling

REPLACEABLE COMPONENTS

1	Front housing
2	Signal terminals
3	PE terminal
4	DC terminals
5	Seal

RATED CURRENT

200A	
250A	
350A	
400A	
600A Liquid cooling	

REPLACEABLE COMPONENTS

1	Front housing	
2	Signal terminals	
3	PE terminal	
4	DC terminals	
5	Seal	

RATED CURRENT

200A	
250A	
300A	
380A	
600A Liquid cooling	





Amphenol PCD Shenzhen

Building C
Dagang Industrial Zone
Guangming District
Shenzhen 518132
China

Tel: +86 755-8173-8000 Email: inquiry@amphenolpcd.com.cn

www.amphenolpcd.com.cn








PLUGS

Ref. No: EV-PLUGS-0625

Note

Amphenol PCD Shenzhen has made every effort to ensure that the information contained in this brochure is accurate at the time of publication. Specifications or information stated in this publication are subject to change without notice.

Amphenol PCD Shenzhen reserves the right to clarify this catalog.



CHARGING